SPECS BY LOCATION/TRADE with Costs

Example ONLY

Bidding Open Date: Bidding Close Date: Initial:		ng Close Date:	Case Number: Project Manager: Phone:				
Addres	ss: 12	3 XYZ Avenue	Unit: L	Jnit 0 1			
Location:		1 - Exterior	Approx. W	/all SF: 1,632		Ceiling/Floor S	F: 1,131
Spe	ec #	Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry					
272	0	STUCCO ON FRAME Install stucco mesh over 2 wraps a 1" coat of colored float finish.		1,600.00	SF	\$3.43	\$5,488.00
298	0	WINDOW-VINYL DBL HNG DE Field measure, order and install a glazed, one-over-one window an interior casing and exterior trim. sized windows.	a vinyl, double hung, double d jamb including screen, caulk,	8.00	EA	\$486.58	\$3,892.64
3184	4	DOOR PREHUNG METAL EN Install an ENERGY STAR certification, with a passage latch and of to match the deadbolts of other en	ed 36" insulated prehung steel double cylinder dead bolt keyed	2.00	EA	\$583.90	\$1,167.80
335	5	Prehung DOOR6 PANEL INT, Install prehung 6-panel, hollow of privacy lockset and 2 1/4 primed frame on second bedroom for pri	core, masonite door, Include d trim, fill holes. Install door	4.00	EA	\$343.47	\$1,373.88
3875	5	HOUSE NUMBER SET Install 3" high metal or PVC hous backer board painted with 2 coats		1.00	EA	\$42.00	\$42.00
3975	5	WHEELCHAIR RAMP Design and construct a preservat ramp complete with 2"x4" safety plywood surface treatment support ground, in conformance with ANS shall not exceed 1'0" rise to 12'0" Submit preliminary drawing to ow Three ramps should be construct door. One from kitchen to Living in the dining area to the bathroom a	handrails and non-slip 3/4" orted by 4"x4" post set 36" in BI recommendations. Slope frun. Minimum inside width, 36" orner for approval. ted. One from exterior to front froom area, and the third from	3.00	SF	\$1,144.90	\$3,434 <u>.</u> 70
Trade:	16	Conservation					
4938	3	R30 After Air Sealing (Spec # 16-4903 (no ammonium sulfate permitted) dense-packed into closed floor ca 3.5 Lbs. per CF. Maintain ventilat other vents with baffles. Replace gain access to match existing ma attic is via a fixed staircase insula interior stairwell walls as part of the	B) Install blow in borax treated cellulose insulation wities to a minimum density of tion routes from soffit and all material removed or cut to terials. NOTE: If access to te stairs to attic, landing &	1,050.00	SF	\$1.14	\$1,197.00

Unit: Unit 01 Address: 123 XYZ Avenue Location: 1 - Exterior Approx. Wall SF: 1,632 Ceiling/Floor SF: 1,131 Spec # **Unit Price Total Price** Spec Quantity Units Trade: 16 Conservation hatch insulate the hatch with 3" of reflective foil faced polyisocyanurate foam and seal edges with compatible foil tape. If access is via a fold down stair insulate the stair with an airtight 2" thick reflective foil faced polyisocvanurate foam box with seams and seal the edges with a compatible foil tape. Trade: 17 Drywall & Plaster 5204 **DRYWALL REPAIRS** 1.00 EA \$3,720.93 \$3,720.93 Repair any drywall damage and texture to match. Paint entire interior of house with Satin, including doors and trim. Trade: 18 Ceramic Tile 5425 CERAMIC FLOOR TILE 900.00 SF \$4.57 \$4,113.00 Remove Existing Flooring. Dispose of in an approved landfill. Repair subfloor as neccessary. Using adhesive, lay owner's choice of \$2/sf ceramic floor tile. Install a 3" marble threshold at door. After at least 24 hours drying time, apply SpectraLOCK® PRO Grout. Clean floor and apply mildew resistant white Low VOC silicone caulk to all edge seams and pipe penetrations. Include base molding installed, caulked, filled, and painted. Trade: 19 Paint & Wallpaper 5679 PREP & PAINT EXTERIOR WOOD--LOW VOC--GCI 1.00 SF \$1,144,90 \$1,144.90 NOTE: Refer TO LEAD HAZARD CONTROL SPECIFICATIONS FOR VACANT STRUCTURES #5503 EXTERIOR PAINT FILM STABILIZATION: Using lead work safe practices remove & properly dispose all loose materials prior to installation of new materials. Using lead work safe practices prepare existing wood surfaces specified for stabilization prior to paint application by securing, replacing or repairing all loose, broken, rotted, or deteriorated materials to provide a sound surface for paint application. Prepare trim surfaces by removing all loose paint using lead work safe practices & according to paint manufacturer's recommendations. Use a 25-year or better paintable Low VOC caulk matched for color to fill all cracks, voids, holes, etc. prior to painting. Apply a compatible exterior Low VOC primer to all bare wood areas. Apply two coats of quality exterior LOW VOC paint to specified wood. All paints and primers must meet the Green Seal G-11 Environmental Standard http://www.greenseal.org/certification/standards/paints.cfm. Adhesives must comply with Rule 1168 of the South Coast Air Quality Management District. All caulks and sealants must comply with regulation 8, rule 51, of the Bay Area Air Quality Management District. Match existing color as close as possible. All work to be done in a neat & professional manner. Use care to protect all surfaces not intended for paint coverage. Trade: 21 HVAC

Address: 12	23 XYZ Avenue	Unit: Un	it 01	9/1-1		
Location:	1 - Exterior	Approx. Wall	SF: 1,6	32	Ceiling/Floor SF: 1,131	
Spec #	Spec	C	Quantity	Units	Unit Price	Total Pric
Trade: 21	HVAC					
6040	FURNACE 90+ GAS - WITH DISTRIBUTION CONDITIONING 13+ SEER Use the Air Conditioning Contractors of Ametest edition of their Manual J Heat loss calculated the post rehab building envelope), use ACC equipment selection and use Manual D for a Make every effort to install supply ducts in inconditioned wall cavities). NOTE: Provide A reports before work begins. Size furnace to considering any areas which may be added the plan. Remove existing furnace or boiler components and dispose of all other material dump. FURNACE: install a 90+ gas fired for minimum AFUE rating of 90% or higher on a new supply and return ductwork work & gas be vented with PVC piping per manufacture. New furnace will have minimum limited warm on heat exchangers; 5 years on parts. Include the mostal controls, vent pipe & new shut-or return air duct ensuring easy access, good for replacement of air filter. An exterior return a installed on one side, both sides, or bottom of Seal all duct joints with Duct Mastic. Include comparable) type swamp cooler. Price to incompore alteration.	erica's (ACCA) late ulation tool e manual J based on A's Manual S for ductwork design. Interior partitions (in Manual J, S and D to the living unit or subtracted from a recycle all metal als in a code legal orced air furnace with 2" patio block to with line. New furnace to a r's specifications. In a code legal orced air furnace to a respective of: 20 years and a line auto set back of valve. Install fit & easy air filter box shall be of new furnace.	1.00	EA	\$8,872.98	\$8,872.9
Trade: 23	Electric					
7402	ELECTRICGENERAL REQUIREMENTS All materials shall be UL approved and/or National Code rated. All drilling, cutting and fastening true, and shall not critically damage framing patching shall match the surrounding surface electrical up to code including GFI in bath an Include new light fixtures inside and outside in bedrooms, kitchen, and living room. Include electric service outside.	g shall be neat and members. All e. Bring ALL nd kitchen areas. Include ceiling fans	1.00	GR	\$6,010.73	\$6,010.73
			L	ocatio.	n Total:	\$40,458.56
Location:	2 - Kitchen	Approx. Wall	SF: 0		Ceiling/Floor S	F: 0
Spec #	Spec	Q	uantity	Units	Unit Price	Total Price
Trade: 22	Plumbing					
7230	Replumb entire kitchen including schedule 4 PVC drain waste vent, PVC or copper supply and fittings to the following fixtures: 33"x 22" gauge stainless steel sink, with a single level year drip-free warranty.	y, shut-off valves " double bowl, 20	1.00	EA	\$1,488.37	\$1,488.37

Address: 123 XYZ Avenue		23 XYZ Avenue Uni	t: Unit 01			
Location:		2 - Kitchen Approx. W		U A	Ceiling/Floor S	BF: 0
Spe	c #	Spec	Quantity	Units	Unit Price	Total Price
Trade:	23	Electric				
7750)	FLUORESCENT LIGHT FIXTURE-Kitchen Install a surface mounted fluorescent fixture with acrylic diff and energy efficient ballast.	1.00 user	EA	\$251.88	\$251.88
Trade:	25	Appliances				
8402	2	APPLIANCESGENERAL REQS.	1.00	GR	\$1,717.35	\$1,717.35
		All appliances shall be enameled steel with energy ratings in upper third of the market.Includes Self-Cleaning Range.Cold Choice is from homeowner			. ,	, ,
			1	Locatio	on Total:	\$3,457.60
Location	n:	3 - Bathroom Approx	. Wall SF: 0		Ceiling/Floor S	F: 0
Spec	: #	Spec	Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry				
3820	}	TOWEL SET 4-PIECE CHROME	1.00	EA	\$150.00	\$150.00
		Install a chrome plated steel bath set comprised of a hook towel ring, 24" towel bar and toilet paper holder. Item 1986 at lowes.	15			
3825	1	Oak Medicine Cabinet 30"	1.00	EA	\$300.00	\$300.00
		Install a 30"I, oak, surface mounted medicine cabinet with gimirror and two shelves.	lass			
3935	i	GRAB BARGENERAL REQUIREMENTS Where installation is on frame wall, secure tightly to studs. If studs cannot be located, open the wall, install blocking and repair wall to original condition. Installation must be capable withstanding stress and weight of a person pulling him/herse up. Grab bars of all stainless steel, 18 gauge, 1-1/4" outside diameter. Grab bars should be installed in shower and by the cammode	of If	EA	\$60.00	\$180.00
Trade:	18	Ceramic Tile				
5425		CERAMIC FLOOR TILE	50.00	SF	\$9.16	\$458.00
		Using adhesive, lay owner's choice of \$2/sf ceramic floor tile over floor. After at least 24 hours drying time, apply SpectraLOCK® PRO Grout. Clean floor and apply mildew resistant color matched silicone caulk to all edge seams and pipe penetrations.				
Trade:	22	Plumbing				
7181		Plumbing bring up to code/bath remeodel Re-plumb entire bath to provide fixtures as follows: 1) WHITE fiberglass tub/shower unit w/ single lever diverter valve, shower head with a maximum 2.0 GPM flow rate & friction fit chrome shower rod; (note: exterior wall sections	1.00	EA	\$6,869.40	\$6,869.40

Address: 123 XYZ Avenue		Unit:	Unit 01			YP TYPE
Location:	3 - Bathroom	Approx. V	Vall SF: 0		Ceiling/Floor	SF: 0
Spec	# Spec		Quanti	ty Units	Unit Price	Total Price
Trade: 2	2 Plumbing					
	behind the tub shower unit must be completed to installation) Include seat and grab bars(of Tiled shower if economically Feasible) 2) Install a 1.3 GPF close coupled, white, it china commode. Include a manufacturer's pressed wood white seat, supply pipe, shu seal. 3) 30" vanity w/ cultured marble integrated backsplash & single lever brass bodied ch maximum 2.0 GPM flow rate. Include PVC code legal plumbing vent, use type L copp stops or PEX supply piping, & escutcheon waste lines.Bring plumbing up to code. Verhas no problems.	Preferred Substitution high boy, vitreous is approved plastic or it-off valve, and wax top, bowl & rome faucet with a drain attached to a er with brass bodied plates on all supply &	n 3			
Trade: 2:	3 Electric					
7761	ENERGY STAR 2 BULB BATH VANITY F Install an Energy Star approved, over vanit the sink.		1.0	0 EA	\$228.98	\$228.98
7820	BATH VENT FAN Install a ceiling or through-the-wall, exterior with damper, and chrome faceplate capable sones. Include; power and switch wiring us Romex. Repair any tear out.	le of 60CFM at 60	1.0	0 EA	\$257.60	\$257.60
				Locatio	on Total:	\$8,443.98
Location:	4 - Bedroom	Approx. W	all SF: 0		Ceiling/Floor S	F: 0
Spec #	Spec		Quantit	y Units	Unit Price	Total Price
Trade: 10	Carpentry					
4160	CLOSETBEDROOM Construct a 28" deep by 3' wide closet in be Hang, tape and 3 coat finish 1/2" gypsum to 2"x 3" framing. Hang a 3'x 6'8" louvered pilincluding overhead track and hardware. Insplywood shelf, 1-3/8" hanger rod and 1"x 4' Match exterior base to room. Prep and pringle-	o both sides of the ine bifold door stall a 1"x 12" " interior base.	1.0	O EA	\$2,633.27	\$2,633.27
				Locatio	n Total:	\$2,633.27
Unit Total for 123XYZ Avenue, Unit Unit 01:						\$54,993.41
Address Grand Total for 123 XYZAvenue:						\$54,993.41
	Bidd	ler:				